



SAFETY DATA SHEET

1. Identification

Product identifier	HEAVY DUTY FLOOR STRIPPER (1:4 DILUTION)	
Other means of identification		
Product number	FL-2100-C / FL-2100-D / FL-2100-E	
Recommended use	Floor polish remover	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	Indiana Correctional Industries (ICI)	
Address	Indiana Department of Correction 1110 South Vestal Drive, P.O. Box 840 Plainfield, IN 46168 United States	
Telephone	317 955-6800 800 736-2550	
Emergency phone number	CHEMTREC	1-800-424-9300

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Not classified
	Acute toxicity, dermal	Not classified
	Acute toxicity, inhalation	Not classified
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
OSHA defined hazards	Not classified.	
Label elements		

Signal word	Warning
Hazard statement	Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.
Prevention	Wear safety glasses with side shields (or goggles). Wear protective gloves. Use only in well-ventilated areas. Wash hands thoroughly after handling.
Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store away from incompatible materials. Keep out of the reach of children.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None known.

HEAVY DUTY FLOOR STRIPPER (1:4 DILUTION)
Product number: FL-2100-C / FL-2100-D / FL-2100-E

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	% by weight
2-Butoxyethanol	111-76-2	5 - <10
Ethanolamine	141-43-5	1 - <5
d-Limonene (Terpene Hydrocarbon)	5989-27-5	0.1 - <1

4. First-aid measures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Take off contaminated clothing and wash before reuse.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Notes to physician	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash. May cause redness and pain.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Precautions for safe handling	Do not get this material in contact with skin. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Ethanolamine (CAS 141-43-5)	STEL	6 ppm
	TWA	3 ppm

Control parameters

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m ³
		50 ppm
Ethanolamine (CAS 141-43-5)	PEL	6 mg/m ³
		3 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls Ensure adequate ventilation, especially in confined areas. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	clear
Form	Liquid.
Color	Yellow green
Odor	mild citrus
Odor threshold	Not available.
pH	11.7
Melting point/freezing point	< 32 °F (< 0 °C)
Boiling point	212 °F (100 °C)
Flash point	None to Boiling
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.

HEAVY DUTY FLOOR STRIPPER (1:4 DILUTION)
Product number: FL-2100-C / FL-2100-D / FL-2100-E

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Solubility(ies)

Solubility (water) 100 %

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Specific gravity 1

VOC (Weight %) 7.2 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Do not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Toxicological data

Product

Test Results

HEAVY DUTY FLOOR STRIPPER (1:4 DILUTION) (Mixture)

Acute Dermal LD50 Rabbit: > 5000 mg/kg

Acute Inhalation LC50 Rat: > 20 mg/l/4h Mist

Acute Oral LD50 Rat: > 5000 mg/kg

Information on likely routes of exposure

Eye contact Causes serious eye irritation.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Ingestion Expected to be a low ingestion hazard.

Inhalation Prolonged inhalation may be harmful.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Skin irritation. May cause redness and pain. Dermatitis. Rash.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2)

3 Not classifiable as to carcinogenicity to humans.

HEAVY DUTY FLOOR STRIPPER (1:4 DILUTION)
Product number: FL-2100-C / FL-2100-D / FL-2100-E

d-Limonene (Terpene Hydrocarbon) (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.
Chronic effects Prolonged inhalation may be harmful. May be harmful if absorbed through skin.
2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Toxicological information Occupational exposure to the substance or mixture may cause adverse effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability No data is available on the degradability of this product.
Bioaccumulative potential No data available.
Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT
Not regulated as dangerous goods.
IATA
Not regulated as dangerous goods.
IMDG
Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)
Not listed.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
Not listed.
CERCLA (Superfund) reportable quantity
Not listed.

HEAVY DUTY FLOOR STRIPPER (1:4 DILUTION)
Product number: FL-2100-C / FL-2100-D / FL-2100-E

16. Other information, including date of preparation or last revision

HMIS Hazard Ratings	
<i>Health:</i>	2
<i>Flammability:</i>	1
<i>Reactivity:</i>	0

Issue date 10-19-2015

Version # 02

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.